Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-051-9664

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
Between 1.332 inches and 1.382 inches	
Overall Height:	
Between 1.554 inches and 1.570 inches	
Overall Width:	
Between 1.554 inches and 1.570 inches	
Environmental Protection:	
Moisture resistant and shock proof and vibration resistant and salt wate	er resistant
Unthreaded Mounting Hole Diameter:	
Between 0.116 inches and 0.126 inches	
Center To Center Distance Between Mounting Facilities Parallel To	o Height:
Between 1.245 inches and 1.255 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To B	ody Width:
Between 1.245 inches and 1.255 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.894 inches and 0.906 inches	
Threaded Device Type:	
Back shell	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
22-14 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
225.0 and 190.0 and 160.0 and 50.0	
Shell Type:	
Solid	
Connector Locking Method:	
Bayonet latch	
Thready Qty Per Inch (tpi):	
28	
Thread Size:	
1.375 inches	



## **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy 6061 **Shell Surface Treatment:** Chromium **Shell Material Specification:** Qq-a-367, comp 6061, t6 federal specification single material response **Included Contact Quantity:** 14 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.014 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Un **Specification Data:** 81349-mil-c-81511/41 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard):

Mil-g-45204 spec.