

View Online at <https://aerobasegroup.com/nsn/5935-01-052-1226>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

Between 1.462 inches and 1.602 inches

**Overall Height:**

1.625 inches

**Overall Width:**

1.625 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.118 inches and 0.124 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.881 inches and 0.911 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-19 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

660.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

940.0 single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

110.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.375 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Insert Material Specification:**

Mil-r-3065 military specification single material response single mating end

**Included Contact Quantity:**

14 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-r-3065 spec.