Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-052-1229

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.462 inches and 1.602 inches
Overall Height:
1.375 inches
Overall Width:
1.375 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.118 inches and 0.124 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.062 inches
Distance From Mounting Shoulder To Front Face:
Between 0.881 inches and 0.911 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-9 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
350.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
490.0 single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid



**Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and copper single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Insert Material Specification:** Mil-r-3065 military specification single material response single mating end **Included Contact Quantity:** 5 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.007 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-r-3065 spec.