Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-052-1231

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.532 inches
Overall Height:
Between 1.610 inches and 1.640 inches
Overall Width:
Between 1.610 inches and 1.640 inches
Environmental Protection:
Corrosion resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.118 inches and 0.124 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.245 inches and 1.255 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.245 inches and 1.255 inches
Distance From Mounting Shoulder To Front Face:
Between 0.750 inches and 0.760 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-9 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1170.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1640.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
145.0
Shell Type:
Solid



Connector Locking Method: Externally threaded shell **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Included Contact Quantity:** 3 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0