NSN 5935-01-052-5155

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-052-5155 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.462 inches and 1.602 inches **Overall Height:** 1.375 inches **Overall Width:** 1.375 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.124 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** Between 0.750 inches and 0.760 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18-11 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 41.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 660.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 940.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0

Shell Type:

Solid

NSN 5935-01-052-5155

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 3



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.125 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 type 11, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 mr cl 4
military specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416 type 11 military specification all treatment responses
Insert Material Specification:
Mil-r-3065 military specification single material response single mating end
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

NSN 5935-01-052-5155

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.