

View Online at <https://aerobasegroup.com/nsn/5935-01-052-5856>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.500 inches

**Overall Diameter:**

0.593 inches

**Environmental Protection:**

Shock proof and vibration proof

**Cable Entrance Diameter:**

0.190 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Frequency Rating:**

4000.0 megahertz single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.