Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-052-6428

View Online at https://aerobasegroup.com/nsn/5935-01-052-6428	
Body Style:	
Right angle type	
Overall Length:	
4.150 inches	
Overall Height:	
0.400 inches	
Unthreaded Mounting Hole Diameter:	
0.120 inches	
Distance Between Mounting Facility Centers:	
3.900 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
2 rows of contacts non-inserted board single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
5.0 single mating end single contact grouping	
Polarization Method:	
Guide pin/socket	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end or plastic phenolic single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204 military specification single treatment response single mating end single contact grouping	
Terminal Type:	
Pin single mating end single contact grouping	
Contact Material Specification:	
Qq-c-530 federal specification single material response single mating end single contact grouping	
Guide Design And Location:	
D shape socket right-hand at 3 oclock	
Insert Material Specification:	
Mil-m-14 military specification 1st material response single mating end or mil-p-19833 military specification 1st material response single	
mating end or mil-m-14 military specification 2nd material response single mating end	
Included Contact Quantity:	
66 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	



Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.066 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.