NSN 5935-01-052-7238

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-052-7238

2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 1.840 inches and 1.860 inches
Overall Height:
Between 0.682 inches and 0.742 inches
Overall Width:
Between 0.240 inches and 0.260 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy 172 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, cl 1, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2
federal specification 2nd treatment response single mating end single contact grouping

NSN 5935-01-052-7238

Electrical Plug Connector - Page 2 of 2



Terminal Ty	ype:
-------------	------

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

30 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.