## NSN 5935-01-053-1487

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-053-1487

Body Style:
Straight type
Overall Length:
3.590 inches
Overall Height:
0.745 inches
Overall Width:
0.425 inches
Unthreaded Mounting Hole Diameter:
0.128 inches
Distance Between Mounting Facility Centers:
3.330 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Shell
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping and qq-n-290 federal specification
single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-750 federal specification single material response single mating end single contact grouping
Shell Guide Type And Location Designator:
3 pin and 191 pin

**Included Contact Type:** 

**Included Contact Quantity:** 

Round pin single mating end single contact grouping

29 single mating end single contact grouping

## NSN 5935-01-053-1487

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.029 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.