

View Online at <https://aerobasegroup.com/nsn/5935-01-053-4029>

**Body Style:**

Straight shape

**Overall Length:**

Between 2.620 inches and 2.650 inches

**Overall Height:**

Between 0.416 inches and 0.436 inches

**Overall Width:**

Between 0.590 inches and 0.620 inches

**Environmental Protection:**

Corrosion resistant and moisture proof and shock resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:**

Between 2.401 inches and 2.411 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"78, 078" single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 type 1, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 type 2, cl 2 federal specification single treatment response

**Insert Material Specification:**

Mil-m-14 sdg-f military specification single material response single mating end

**Included Contact Quantity:**

78 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Furnished items - insertion-extraction tool

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.078 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-24308/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.