

View Online at <https://aerobasegroup.com/nsn/5935-01-053-4041>

Body Style:

Pcb, angle shape, external coupling

Overall Length:

0.415 inches

Overall Height:

0.385 inches

Environmental Protection:

Shock proof and vibration proof

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Detent

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-4204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-4204 spec.