## NSN 5935-01-054-0864



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-054-0864 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Hood, side opening w/clamp **Overall Length:** 2.530 inches **Overall Height:** 1.787 inches **Overall Width:** 0.875 inches **Environmental Protection:** Corrosion resistant and thermal shock resistant and vibration resistant **Cable Entrance Diameter:** 0.608 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 56 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 8.5 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Hood, side opening **Connector Locking Method:** Post jacksocket **Connector Cable Strain Relief Method:** Cable clamp **Thread Size:** 0.125 inches **Terminal Location:** Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-054-0864

Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Milg-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-b-750 comp a federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Insert Material Specification:
Mil-m-14f, ty sdg-f military specification single material response single mating end
Included Contact Quantity:
56 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.054 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

spec.