## NSN 5935-01-054-5321

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-054-5321

**Body Style:** Straight shape, internal coupling Overall Length: 1.450 inches Overall Diameter: 1.810 inches **Mating End Quantity: Contact Position Arrangement Style:** 16-23 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Spring friction **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification all treatment responses **Shell Material Specification:** 

## Qq-a-225/9 federal specification single material response Included Contact Quantity:

1 single mating end 1st contact grouping22 single mating end 2nd contact grouping

## **Included Contact Type:**

Round socket single mating end all contact groupings

## NSN 5935-01-054-5321

Electrical Plug Connector - Page 2 of 2



Special Features:
Lanyard release
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.027 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.027 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.