## NSN 5935-01-055-9242

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-055-9242

**Body Style:** Right angle type **Overall Length:** 4.940 inches Overall Width: Between 0.310 inches and 0.330 inches **Body Height:** Between 0.228 inches and 0.248 inches **Environmental Protection:** Moisture resistant and shock resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 300.0 single mating end single contact grouping **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 11 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** 

Qq-b-750 comp a federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, ty sdg-f military specification single material response single mating end

## NSN 5935-01-055-9242

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
98 single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.098 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.