

View Online at <https://aerobasegroup.com/nsn/5935-01-056-0196>

Body Style:

Straight shape, external coupling

Overall Length:

1.049 inches

Overall Height:

Between 1.021 inches and 1.041 inches

Overall Width:

Between 1.021 inches and 1.041 inches

Unthreaded Mounting Hole Diameter:

Between 0.110 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

Distance From Mounting Shoulder To Front Face:

0.800 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Oct-98 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel alloy single mating end single contact grouping

Contact Surface Treatment:

Nickel single mating end single contact grouping and gold single mating end single contact grouping

Contact Surface Treatment Specification:

Qq-n-290, cl 2 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Mil-i-23011, cl 2 military specification single material response single mating end single contact grouping

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

U-pin single mating end single contact grouping

Test Data Document:

98230-0n199139 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-i-23011 spec.