

View Online at <https://aerobasegroup.com/nsn/5935-01-056-4234>

**Thread Class:**

2a

**Body Style:**

Straight shape, external coupling

**Unable To Decode:**

Unable to decode and unable to decode

**Overall Length:**

0.700 inches

**Overall Diameter:**

0.240 inches

**Distance From Mounting Shoulder To Front Face:**

0.450 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Sm single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

750.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

5.0 megahertz single mating end single contact grouping

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533, cond h federal specification single material response single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Passivate

**Shell Surface Treatment Specification:**

Qq-p-35, type 2 federal specification single treatment response

**Shell Material Specification:**

Qq-s-764, type 303, cond a federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Special Features:**

Receptacle mates with 578r669h01

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.