# NSN 5935-01-056-6263

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-056-6263

view Online at https://aerobasegroup.com/nsn/5955-01-056-6265
Body Style:
Straight shape, internal coupling
Overall Length:
0.766 inches
Overall Diameter:
1.406 inches
Environmental Protection:
Fungus proof
Mating End Quantity:
1
Contact Position Arrangement Style:
18-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Compression nut
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
66 single mating end single contact grouping
Included Contact Type:

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

Round pin single mating end single contact grouping

## NSN 5935-01-056-6263

Electrical Plug Connector - Page 2 of 2



#### **Precious Material And Weight:**

0.066 gold grains, troy and 0.066 silver grains, troy

**Precious Material:** 

Gold and silver

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

96906-ms27484 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.