NSN 5935-01-057-7567

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-057-7567

Body Style: Straight type **Overall Length:** 9.150 inches **Overall Height:** 1.185 inches **Overall Width:** 0.420 inches **Unthreaded Mounting Hole Diameter:** Between 0.127 inches and 0.133 inches **Distance Between Mounting Facility Centers:** 8.900 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Guide pin/socket **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Contact Surface Treatment Specification:** Mil-g-45204 type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-533 federal specification single material response single mating end single contact grouping **Guide Design And Location:** D shape pin right-hand at 11 oclock **Insert Material Specification:** L-p-410 federal specification single material response single mating end

Included Contact Quantity:

110 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

NSN 5935-01-057-7567

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.110 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.