## NSN 5935-01-058-0782

Telephone Jack - Page 1 of 2

**Terminal Type:** Tab, solder lug



View Online at https://aerobasegroup.com/nsn/5935-01-058-0782 **Thread Class:** 2b **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated from panel **Body Style:** Dual hole or slot mounted **Overall Length:** 2.562 inches **Overall Height:** 1.015 inches **Mounting Hole Diameter:** 0.112 inches **Mounting Bushing Length:** 0.375 inches **Body Width:** 0.281 inches **Distance Between Mounting Facility Centers:** 0.812 inches **Bushing Accommodation Hole Shape:** Double round plain **Accommodated Finger Type:** Two conductor, slender round tip all fingers **Finger Accommodation Diameter:** 0.1755 inches all fingers and 0.1757 inches all fingers **Finger Accommodation Length:** 0.780 inches all fingers **Center To Center Distance Between Finger Accommodations:** 0.312 inches Center To Center Distance Between Bushing Thru-hole Accommodations: 0.312 inches **Jack Contact Arrangement Designator:** J7 **Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches

## NSN 5935-01-058-0782

Telephone Jack - Page 2 of 2



Material:
Steel body
Material:
Steel body
<b>Precious Material And Location:</b>
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.020 gold grains, troy
Precious Material:
Gold
Surface Treatment:
Tin terminal
Surface Treatment:
Gold contact
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03400