

View Online at <https://aerobasegroup.com/nsn/5935-01-058-2266>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape quick connect

**Overall Length:**

1.562 inches

**Overall Width:**

0.800 inches

**Overall Diameter:**

0.800 inches

**Environmental Protection:**

Corrosion resistant and shock resistant and moisture resistant and thermal shock resistant and vibration resistant

**Distance From Mounting Shoulder To Front Face:**

0.697 inches

**Mounting Facility Thickness:**

Between 0.055 inches and 0.275 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Bnc all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

4000.0 megahertz all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.500 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic polyamide all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 2 military specification single treatment response all mating ends single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Chromate

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Special Features:**

Pressurized, weatherproof seal-30 psi, max

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

81349-mil-c-55339/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.