Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-058-4097

view Online at https://aerobasegroup.com/nsn/5935-01-058-4097
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle, shape, internal coupling
Overall Length:
1.156 inches
Overall Height:
0.675 inches
Overall Diameter:
0.312 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Shrinkable tubing
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-01-058-4097 Electrical Plug Connector - Page 2 of 2



Crimp sing	gle mating end single contact grouping
Contact I	Material Specification:
Qq-c-530	federal specification single material response single mating end single contact grouping
Shell Sur	face Treatment:
Passivate	
Insert Ma	terial Specification:
Mil-p-1940	68 military specification single material response single mating end
Included	Contact Quantity:
1 single m	nating end single contact grouping
Included	Contact Type:
Coaxial pi	in single mating end single contact grouping
Precious	Material And Location:
Contact s	urface gold
Precious	Material And Weight:
0.005 gold	d grains, troy
Precious	Material:
Gold	
Thread S	eries Designator:
Uns	
Shelf Life	2:
N/a	
Unit Of M	leasure:
Demilitar	ization:
No	
Fiig:	
A039b0	
Mil-std (n	nilitary Standard):
Mil-g-452	04 spec.