NSN 5935-01-058-4099

Overall Length: 7.150 inches Overall Height: 0.550 inches Overall Width: 0.250 inches

0.120 inches

Environmental Protection:

Shock proof and vibration resistant

Unthreaded Mounting Hole Diameter:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-058-4099

| Distance Between Mounting Facility Centers: |
|--|
| 3.450 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-c-530 federal specification single material response single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-14, type sdg-f military specification single material response single mating end |
| Included Contact Quantity: |
| 120 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| |

NSN 5935-01-058-4099

Electrical Receptacle Connector - Page 2 of 2



| Precious Material: |
|------------------------------|
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |

Mil-g-45204 spec.