

View Online at <https://aerobasegroup.com/nsn/5935-01-058-4689>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape

**Overall Height:**

0.955 inches

**Environmental Protection:**

Vibration resistant and shock resistant and thermal shock resistant and corrosion resistant and moisture resistant

**Cable Entrance Diameter:**

0.234 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Sma single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

335.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

12400.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Crimp type

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic fluorocarbon single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold and copper

**Shell Surface Treatment Specification:**

Mil-g-45204, cl 1, type 1, grade c military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

**Shell Material Specification:**

Qq-c-530 federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Special Features:**

Solder flange mtd

**Precious Material And Location:**

Contact, shell, nut, disc and lockwasher surfaces gold

**Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.