

View Online at <https://aerobasegroup.com/nsn/5935-01-058-4690>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.685 inches

Overall Diameter:

0.375 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

Cable Entrance Diameter:

0.088 inches

Distance From Mounting Shoulder To Front Face:

0.450 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

18000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response

Shell Material Specification:

Qq-s-764, class 303, cond a federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact @and shell surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.