

View Online at <https://aerobasegroup.com/nsn/5935-01-058-4980>

Body Style:

Right angle type

Overall Length:

Between 9.148 inches and 9.152 inches

Overall Width:

0.518 inches

Environmental Protection:

Moisture proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.094 inches

Distance Between Mounting Facility Centers:

8.900 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Milg-45204 type 2, class 1 military specification 2nd treatment response single mating end single contact grouping and qq-n-290 federal specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 type 2, class 2 military specification single treatment response

Insert Material Specification:

L-p-410 federal specification single material response single mating end

Included Contact Quantity:

110 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

spec.