NSN 5935-01-058-6513

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-058-6513

Body Style:
Straight type
Overall Length:
6.505 inches
Overall Height:
0.715 inches
Overall Width:
0.298 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.096 inches and 0.101 inches
Distance Between Mounting Facility Centers:
6.215 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2
federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Insert Material Specification:
Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single
mating end
Included Contact Quantity:
150 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping

0.150 gold grains, troy

Contact surfaces gold

Precious Material And Location:

Precious Material And Weight:

NSN 5935-01-058-6513

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/25	government	specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.