## NSN 5935-01-058-6513

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-058-6513

Body Style:
Straight type
Overall Length:
6.505 inches
Overall Height:
0.715 inches
Overall Width:
0.298 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.096 inches and 0.101 inches
Distance Between Mounting Facility Centers:
6.215 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2
federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Insert Material Specification:
Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single
mating end
Included Contact Quantity:
150 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping

0.150 gold grains, troy

Contact surfaces gold

**Precious Material And Location:** 

**Precious Material And Weight:** 

## NSN 5935-01-058-6513

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-c-55302/25	government	specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.