# NSN 5935-01-058-7661



Electrical Receptacle Connector Body - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-058-7661 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Rectangular shape **Overall Length:** 3.880 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.500 inches **Overall Height:** 0.900 inches **Overall Width:** 2.000 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** 0.150 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 25-104 single mating end **Polarization Method:** Jackscrew and shell Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 32 **Thread Size:** 0.164 inches and 0.164 inches and 0.138 inches **Insert Material:** 

Plastic diallyl phthalate single mating end

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Anodize and dichromate potassium

# NSN 5935-01-058-7661

Electrical Receptacle Connector Body - Page 2 of 2



#### **Shell Material Specification:**

Qq-a-250 federal specification single material response

#### **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

#### **Shell Guide Type And Location Designator:**

A slot

#### **Unable To Decode:**

Unable to decode and unable to decode

### **Special Features:**

Items furnished as accessories -mounting plate

#### **Thread Series Designator:**

Unc and unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.