

View Online at <https://aerobasegroup.com/nsn/5935-01-058-9254>

**Body Style:**

Straight shape

**Overall Length:**

5.094 inches

**Overall Height:**

0.547 inches

**Overall Width:**

0.438 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and vibration resistant and shock resistant and fungus resistant and dust resistant and sand resistant

**Unthreaded Mounting Hole Diameter:**

0.144 inches

**Distance Between Mounting Facility Centers:**

4.688 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

35 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

725.0 single mating end single contact grouping

**Polarization Method:**

Shell

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium and iridium

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Insert Material Specification:**

Mil-m-14 type mdg military specification single material response single mating end

**Shell Guide Type And Location Designator:**

E slot

**Included Contact Quantity:**

35 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.035 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.