NSN 5935-01-058-9262

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-058-9262

Body Style:
Straight shape
Overall Length:
2.088 inches
Overall Height:
0.554 inches
Overall Width:
0.494 inches
Environmental Protection:
Heat resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
1.852 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
25 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type ii class 1 military specification 1st treatment response single mating end single contact grouping and qq-s-365 grade b
federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:

Contact Material Specification:

Solder well single mating end single contact grouping

Qq-b-626 federal specification single material response single mating end single contact grouping

NSN 5935-01-058-9262

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification single treatment response
Shell Material Specification:
Qq-s-698 federal specification single material response
Insert Material Specification:
Mil-m-19833 military specification single material response single mating end
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.025 gold grains, troy and 0.025 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.