NSN 5935-01-058-9264

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-058-9264

Body Style:
Straight type
Overall Length:
5.094 inches
Overall Height:
0.609 inches
Overall Width:
0.438 inches
Environmental Protection:
Dust resistant and pressure proof and salt water resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.144 inches
Distance Between Mounting Facility Centers:
4.688 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
725.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-058-9264

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

35 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.035 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0