1

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-058-9266

Body Style: Right angle type **Overall Length:** 3.040 inches **Overall Width:** Between 0.310 inches and 0.330 inches **Body Height:** Between 0.140 inches and 0.160 inches **Environmental Protection:** Moisture resistant and salt water resistant and thermal shock resistant and vibration resistant Mating End Quantity: **Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 300.0 single mating end single contact grouping **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-q-45204, type 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 30 single mating end single contact grouping **Included Contact Type:** Flat socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold



Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.