

View Online at <https://aerobasegroup.com/nsn/5935-01-058-9267>

**Body Style:**

Right angle type

**Overall Length:**

2.040 inches

**Overall Width:**

Between 0.310 inches and 0.330 inches

**Body Height:**

Between 0.140 inches and 0.160 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and thermal shock resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 single mating end single contact grouping

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification single material response single mating end

**Included Contact Quantity:**

20 single mating end single contact grouping

**Included Contact Type:**

Flat socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.