# NSN 5935-01-059-1698

Between 2.140 inches and 2.160 inches

Between 0.659 inches and 0.699 inches

**Thread Class:** 

Body Style: Straight shape Overall Length:

**Overall Height:** 

Overall Width: 0.250 inches

**Environmental Protection:** 

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-059-1698

Shock resistant
Distance Between Mounting Facility Centers:
1.950 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Length:
0.140 inches
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Front single mating end single contact grouping
Contact Material:
Copper alloy 534 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-c-55302 military specification single treatment response single mating end single contact grouping

## NSN 5935-01-059-1698

Electrical Receptacle Connector - Page 2 of 2



Terminal <sup>*</sup>	Type:
-----------------------	-------

Pin single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

## **Included Contact Quantity:**

14 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material:**

Gold

## **Test Data Document:**

98230-0n503088-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Thread Series Designator:**

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-c-55302 spec.