## NSN 5935-01-059-5437

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-059-5437               |
|---|
| Thread Class:   |
| 2b  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight shape, external coupling   |
| Overall Length:   |
| 0.719 inches  |
| Overall Height:   |
| 0.828 inches  |
| Overall Width:  |
| 0.828 inches  |
| Environmental Protection:   |
| Vibration resistant and humidity resistant                                  |
| Unthreaded Mounting Hole Diameter:  |
| 0.120 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Height:   |
| 0.594 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.594 inches  |
| Distance From Mounting Shoulder To Front Face:                              |
| 0.447 inches  |
| Threaded Device Type:   |
| Back shell  |
| Mating End Quantity:  |
| 1   |
| Contact Removability:   |
| Removable single mating end single contact grouping                         |
| Polarization Method:  |
| Keyway or multiple keyway   |
| Insert Position In Deg:   |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Bayonet pin   |
| Thready Qty Per Inch (tpi):   |
| 28  |
| Thread Size:  |
| 0.500 inches  |
| Terminal Location:  |

Back single mating end single contact grouping

## NSN 5935-01-059-5437

Fiig: A039b0

Mil-std (military Standard):

Mil-c-38999 spec.

Electrical Receptacle Connector - Page 2 of 2



| Contact Material:  |
|--|
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Cadmium single mating end single contact grouping and nickel single mating end single contact grouping                                       |
| Insert Material:   |
| Plastic epoxy single mating end  |
| Terminal Type:   |
| Crimp single mating end single contact grouping  |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:   |
| Cadmium and nickel   |
| Included Contact Quantity:   |
| 6 single mating end single contact grouping  |
| Included Contact Type:   |
| Round pin single mating end single contact grouping  |
| Test Data Document:  |
| 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| Unef   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |