## NSN 5935-01-060-5427

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-060-5427

Body Style:
Right angle type
Overall Length:
3.350 inches
Overall Width:
0.359 inches
Body Height:
0.400 inches
Environmental Protection:
Heat resistant and cold resistant and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
End Application:
Model aircraft p-3c
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping

**Guide Design And Location:** 

D shape socket right-hand at 12 oclock

**Insert Material Specification:** 

Mil-m-14, ty gdi 30f military specification single material response single mating end

## NSN 5935-01-060-5427

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 60 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.060 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.