

View Online at <https://aerobasegroup.com/nsn/5935-01-061-1475>

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

1.156 inches

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14-15 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Connector End:**

2.381 inches

**Distance From Centerline To Cable End:**

1.688 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and copper single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response

**Included Contact Quantity:**

14 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.019 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.