

View Online at <https://aerobasegroup.com/nsn/5935-01-061-9742>

Body Style:

Straight type

Overall Length:

3.505 inches

Overall Height:

0.571 inches

Overall Width:

Between 0.242 inches and 0.248 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.096 inches and 0.101 inches

Distance Between Mounting Facility Centers:

3.215 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 2, grade c, cl 1 military specification 2nd treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 1st treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-f14 military specification single material response single mating end or mil-p-19833 military specification single material response single mating end

Included Contact Quantity:

70 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.070 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.