

View Online at <https://aerobasegroup.com/nsn/5935-01-061-9743>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.111 inches

Environmental Protection:

Moisture resistant and shock proof and vibration proof

Mounting Facility Thickness:

0.160 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

32 and 28

Thread Size:

0.375 inches and 0.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class i military specification 1st treatment response single mating end single contact grouping and mil-c-14550 class 4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Turret single mating end single contact grouping

Contact Material Specification:

Qq-b-626 comp 360 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and copper alloy

Shell Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class i military specification 1st treatment response and mil-c-14550 class 4 military specification 2nd treatment response

Shell Material Specification:

Qq-b-626 comp 360 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.