# NSN 5935-01-062-2383

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-062-2383

**Body Style:** 

Angle shape, pcb type

**Overall Length:** 

3.425 inches

**Overall Height:** 

0.359 inches

**Overall Width:** 

0.250 inches

#### **Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

0.120 inches

#### **Distance Between Mounting Facility Centers:**

2.725 inches

#### **Mating End Quantity:**

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

#### **Connector Locking Method:**

Friction

#### **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Contact Surface Treatment Specification:**

Qq-n-290 class 2 federal specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

#### **Guide Design And Location:**

D shape socket left-hand at 3 oclock

#### **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end and mil-p-19833 military specification single material response single mating end

## **Included Contact Quantity:**

100 single mating end single contact grouping

# NSN 5935-01-062-2383

Mil-std (military Standard):

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
8134955302/59 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0