Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-062-2401

Body Style:

Straight shape, external coupling

Overall Length:

1.096 inches

Overall Height:

0.700 inches

Overall Width:

0.700 inches

Environmental Protection:

Shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.106 inches and 0.113 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.450 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Distance Dei

0.450 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Turret single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

3 mounting holes



Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.