NSN 5935-01-062-2426

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-062-2426

| view Offilite at https://defobasegroup.com/nsi//0905-01-002-2-420 |
|--|
| Body Style: |
| Right angle type |
| Overall Length: |
| 0.950 inches |
| Overall Height: |
| 0.660 inches |
| Overall Width: |
| 0.382 inches |
| Environmental Protection: |
| Humidity resistant and thermal shock resistant and moisture resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.106 inches |
| Distance Between Mounting Facility Centers: |
| 0.780 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 1.0 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic polyester single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Included Contact Quantity: |
| 10 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |

Contact surfaces gold

Precious Material And Location:

NSN 5935-01-062-2426

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Weight: |
|--------------------------------------|
| 0.010 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.