## NSN 5935-01-062-2431

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-062-2431 **Body Style:** Straight shape, external coupling strain relief **Overall Height:** 2.250 inches **Overall Width:** 2.250 inches **Body Length:** 3.031 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Mating End Quantity: Contact Position Arrangement Style:** 32-2010-10 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 250.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Cable clamp **Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Rubber single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Included Contact Quantity:** 

54 single mating end single contact grouping

## NSN 5935-01-062-2431

Electrical Receptacle Connector - Page 2 of 2



Incl	lude	<b>A</b> C	ont	act	αvΤ	Δ.
INC	ıuae	ea C	Ont	act	IVD	e.

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.054 gold grains, troy and 0.054 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0