## NSN 5935-01-062-4849

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-062-4849 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.844 inches **Overall Diameter:** 1.766 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 24-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 15.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.219 inches **Thread Size:** 1.437 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** 

Onen material

Aluminum alloy

## NSN 5935-01-062-4849

Mil-c-38999 spec.

Electrical Plug Connector - Page 2 of 2



| Shell Surface Treatment:   |
|--|
| Cadmium  |
| Shell Surface Treatment Specification:   |
| Qq-p-416 federal specification single treatment response   |
| Included Contact Quantity:   |
| 128 single mating end single contact grouping  |
| Included Contact Type:   |
| Round pin single mating end single contact grouping  |
| Precious Material And Location:  |
| Contact surface gold and contact surface silver  |
| Precious Material And Weight:  |
| 0.128 gold grains, troy and 0.128 silver grains, troy  |
| Precious Material:   |
| Gold and silver  |
| Test Data Document:  |
| 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| Unef   |
| Specification Data:  |
| 96906-ms27484 government standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):   |