Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-063-4406

Thread Class	
2b	
Thread Direct	ion:
Right-hand	
Body Style:	
Straight shape	, internal coupling
Overall Lengt	h:
1.213 inches	
Environmenta	Il Protection:
Moisture proof	and salt water resistant and shock proof and vibration proof
Threaded Dev	ісе Туре:
Coupling facilit	У
Mating End Q	uantity:
1	
Contact Posit	ion Arrangement Style:
Rf single matir	ig end
Contact Remo	ovability:
Nonremovable	single mating end single contact grouping
Shell Type:	
Solid	
Connector Lo	cking Method:
Internally threa	ided coupling ring
Connector Ca	ble Strain Relief Method:
Compression i	nut
Radio Freque	ncy Type Contact Characteristic Impedance In Ohms:
50.0 single ma	ting end single contact grouping
Thready Qty I	Per Inch (tpi):
36	
Thread Size:	
0.250 inches	
Terminal Loca	ation:
Back single ma	ating end single contact grouping
Contact Mate	
Copper alloy s	ingle mating end single contact grouping
	ce Treatment:
Gold single ma	ating end single contact grouping
Insert Materia	
	afluoroethylene single mating end
	ce Treatment Specification:
	rpe 2, grade c or d, class 2 military specification single treatment response single mating end single contact groupin
Terminal Type	
	gle mating end single contact grouping

Electrical Plug Connector - Page 2 of 2



Contact Material Specification:

Qq-c-530, condition a or h federal specification single material response single mating end single contact grouping

•	
Shell Material	:
Steel	
Shell Surface	Treatment:
Gold	
Shell Surface	Treatment Specification:
Mil-g-45204, ty	vpe 2, grade c or d, class 1 military specification single treatment response
Shell Material	Specification:
Qq-s-764 fede	ral specification single material response
Insert Materia	I Specification:
Mil-p-19468 m	ilitary specification single material response single mating end
Included Con	tact Quantity:
1 single mating	g end single contact grouping
Included Con	tact Type:
Coaxial pin sin	gle mating end single contact grouping
Precious Mate	erial And Location:
Contact and be	ody surfaces gold
Precious Mate	erial And Weight:
0.105 gold gra	ins, troy
Precious Mate	erial:
Gold	
Thread Series	B Designator:
Uns	
Shelf Life:	
N/a	
Unit Of Measu	ıre:
Demilitarizatio	on:
No	
Fiig:	
A039b0	
Mil-std (milita	ry Standard):
Mil-g-45204 sp	bec.