NSN 5935-01-063-4412

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-063-4412 **Body Style:** Straight shape, external coupling **Overall Length:** 1.019 inches **Overall Height:** 1.141 inches **Overall Width:** 1.141 inches **Environmental Protection:** Weather resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.901 inches and 0.911 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.901 inches and 0.911 inches **Distance From Mounting Shoulder To Front Face:** Between 0.578 inches and 0.598 inches **Mating End Quantity: Contact Position Arrangement Style:** 14-15 single mating end **Contact Removability:** Nonremovable single mating end 2nd contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Split **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end 2nd contact grouping **Contact Material:** Iron single mating end 2nd contact grouping **Contact Surface Treatment:**

Gold single mating end 2nd contact grouping

Terminal Type:
Solder well single mating end 2nd contact grouping

NSN 5935-01-063-4412

Electrical Receptacle Connector - Page 2 of 2



| Shell Material: |
|---|
| Steel |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 14 single mating end 2nd contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| Included Contact Type: |
| Round socket single mating end 2nd contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.015 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |