

View Online at <https://aerobasegroup.com/nsn/5935-01-063-4452>

Body Style:

Straight type

Overall Length:

7.800 inches

Overall Height:

0.888 inches

Overall Width:

0.580 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.073 inches

Distance Between Mounting Facility Centers:

7.600 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-613, comp 2 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 6063

Shell Surface Treatment:

Oxide film

Shell Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Shell Material Specification:

Qq-a-200/9 federal specification single material response

Insert Material Specification:

Mil-m-20693 military specification single material response single mating end

Included Contact Quantity:

110 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Special Features:

Polarized at positions a-e

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.