## NSN 5935-01-063-5107

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-063-5107

**Body Style:** 

Straight edge type w/card guide

**Overall Length:** 

3.275 inches

Overall Width:

0.330 inches

**Body Height:** 

0.437 inches

**Board Accommodated Length:** 

3.107 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.071 inches

**Mating End Quantity:** 

4

#### **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## **Contact Maximum Dc Voltage Rating In Volts:**

600.0 single mating end single contact grouping

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 ty ii military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Tab, solder lug single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

## **Included Contact Quantity:**

60 single mating end single contact grouping

## **Included Contact Type:**

Leaf spring single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

# NSN 5935-01-063-5107

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.060 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.