Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-063-5108

Thread Class: 2b **Thread Direction: Right-hand Body Style:** Straight edge type w/mounting flange **Overall Length:** 3.875 inches **Overall Height:** 0.817 inches **Overall Width:** 0.330 inches **Distance Between Mounting Facility Centers:** 3.757 inches **Board Accommodated Length:** 3.107 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** Between 0.054 inches and 0.071 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 600.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:**

Plastic diallyl phthalate single mating end



Contact Surface Treatment Specification: Mil-g-45204 ty ii military specification single treatment response single mating end single contact grouping **Terminal Type:** Tab, solder lug single mating end single contact grouping **Insert Material Specification:** Mil-m-14 military specification single material response single mating end **Included Contact Quantity:** 60 single mating end single contact grouping **Included Contact Type:** Leaf spring single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.060 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.