

View Online at <https://aerobasegroup.com/nsn/5935-01-064-1123>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.340 inches

**Overall Diameter:**

0.500 inches

**Environmental Protection:**

Shock proof and vibration proof

**Distance From Mounting Shoulder To Front Face:**

0.560 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

50.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet shell

**Connector Cable Strain Relief Method:**

Compression nut

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Contact Surface Treatment Specification:**

Qq-s-365a federal specification single treatment response single mating end single contact grouping

**Terminal Type:**

Turret single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, alloy 360, 1/2 hard federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Body and contact surfaces silver

**Precious Material And Weight:**

0.005 silver grains, troy

**Precious Material:**

Silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0